# Specifications and Optional Extras

Product Specifications:				
Parameter	Resolution	Accuracy	Range	
Carbon Monoxide (Infrared)	0.01%	$\pm 5\%$ of reading *1 $\pm 0.06\%$ volume *1	0-10% Over-range 20%	
Oxygen (Fuel Cell)	0.01%	$\pm 5\%$ of reading *1 $\pm 0.1\%$ volume *1	0-21%	
Hydrocarbon *2 (Infra Red)	1ppm	$\pm 5\%$ of reading *1 $\ \pm 12\%$ volume *1	0-5,000ppm Over-range 20,000ppm	
Carbon Dioxide (Infra Red)	0.1%	±5% of reading *1 ±0.5% volume *1	0-16% Over-range 20%	
NOx *3 (Electro-Chemical)	1ppm	0-4,000ppm ±4% or 25ppm *1 4,000-5,000ppm ±8% *1	0-5,000ppm	
Oil Temperature Optional: (only on some models)	1°C/F	$\pm 2^{\circ}C \pm 0.3\%$ of reading $\pm 4^{\circ}F \pm 0.3\%$ of reading	0-150°C 32-302°F	
RPM Optional: (only on some models)	1rpm	50rpm	200-6,000rpm	
Lambda AFR Petrol AFR LPG	0.001 0.01		0.8-1.2 11.76-17.64 12.48-18.72	

		15-61 70	
15 Sec	onds		

\*1 Using dry gases at STP \*2 Applies only to Petrol and LPG \*3 Applies to 5 Gas models only

Sensor Response T95 (Class 1)	15 Seconds		
Pre-programmed Fuels	Petrol (Gasoline), LPG, CNG and Diesel		
Dimensions Weight Handset Probe	1.1kg 220 x 55 x 120mm Insertion depth 350mm x Dia 15mm Clip handle to secure to exhaust, 4m long hose		
Ambient Operating Range	+5°C to +45°C/10% to 90% RH non condensing		
Storage Temperature	Minimum 0°C Maximum +50°C		
Battery Charger	Input 110 Vac/230 Vac nominal Output 10 Vac off load		
Analyser Battery Run Time	>4 hours from full charge with the pump running		

	Optional Extras	
	KMIRP	Infrared Printer with thermal printer and AA batteries
	KANE IMPRINT	Infrared Printer with standard paper roll and ink ribbon, supplied with rechargeable batteries, battery charger and 2 paper rolls
	NOX4-1	NOx upgrade for Auto 4-1
	NOX4-2	NOx upgrade for Auto 4-2
	AUTOSWKIT	Auto software kit with CL3 lead for PC interface
	14102/2	Laptop style carry case
	17590	Metal Carry Case
	EPAUTO3	High temp. EPAUTO2 probe with 17702 inline filter
E	EPAUT05	High temp. probe with black hose
	EPAUTO6	Motorbike Probe with emission temperature measurement



Available from:

#### Warranty

All Kane products are warranted from the date of purchase. This warranty covers any defects in materials or manufacturing and applies worldwide.

Kane Automotive is a division of Kane International Limited who specialise in the design and manufacture of electronic instruments for monitoring and optimising both energy usage and emissions from energy processes. Our Policy is to continuously develop and improve our products and so we reserve the right to change any part of our specifications without prior notice.





#### Kane International Limited

Kane House, Swallowfield, Welwyn Garden City, Hertfordshire, AL7 1JG, United Kingdom Tel: +44 (0) 1707 375550 Fax: +44 (0) 1707 393277 Email: sales@kane.co.uk Web: www.kane.co.uk







CE it's easy with Kane

Issued October 2005.

# Hand Held Exhaust Gas Analysers Making emission testing easy and affordable

CO : CO2:

0

0.01 15.0 .015

HCh: 02 :

RPM:

GAS ANALYSER

96 0.41

18

it's easy with Kane

720

MCHEEC



# i iec Exh





Located in the United Kingdom, Kane International Ltd specialise in the design and manufacture of electronic instruments for monitoring and optimising both energy usage and emissions from energy processes.

The Kane Auto 4 & 5 Series Exhaust Gas Analysers are truly portable that set new standards of convenience and ease of use. Weighing just 1Kg, the handset fits comfortably in the hand and can run for up to 4 hours on its internal re-chargeable battery. A multi-functional gas analyser ideal for emission diagnostics, tuning, pre-compliance testing and for regulated testing where OIML R99 Class 1 standards are specified.

The programmed re-calibration procedure permits low cost servicing either on site or at approved service facilities. The O2 and NO sensors are warranted for 2 years from date of purchase. Each analyser is preprogrammed with five language options from a current choice of 10 European languages.

#### 1 So easy to use

Once the analyser has been set-up, there is no need for daily setting or configuration. As a truly portable analyser, you decide where to test. Using the multi fuel selection mode, you can choose between Petrol (Gasoline), LPG, CNG, and Diesel settings.

#### 7 Long life battery

9 Nitrogen Oxides (NOx) Testing

analyser with you on a road test.

and analysed at a later date.

The testing of Nitrogen Oxides is becoming

more relevant. In order to achieve a "NOx"

under a load. This would normally involve

using a dynamometer or taking your gas

With a Kane hand held analyser this is a

reading the vehicle being tested needs to be

A fully charged battery has the capacity to allow the analyser to be used all day without the need to recharge. The battery can be charged via the mains or a vehicles 12 volt battery.

#### 8 Additional features

Lambda/AFR measurement Corrected CO RPM and Oil/Exhaust gas temperature measurements Multi lingual software.

#### 2 Measures

Carbon Monoxide, Hydrocarbons, Carbon Dioxide and Oxygen. Nitrogen Oxides measurement is available on

5 gas models and can be fitted retrospectively to 4 gas models.

#### **8** Fast start up

The analyser is ready to go in just 150 seconds from first power on. Re-zeroing takes just 30 seconds.

4 Full Infra Red Measuring Bench Unlike some portables which calculate CO2 the infra red gas measuring bench measures all three infra red gases (CO, HC and CO2) to give true 4 or 5 gas capability. Oxygen and NOx are measured using automotive electrochemical sensors.

> **5** Logging and Auto-Logging The analyser can store up to 255 sets of full can be recorded manually by the press of a key, or automatically timed so that during a drive test no driver intervention is required. They can then be downloaded to a PC (using

#### **6** PC compatible

The analyser also provides an RS232 output so that using optional PC software, data can be displayed on a PC screen and the PC's printer can be used to produce high quality test reports.

test results in its internal memory. Test results optional software).



A		DATE		15-07-05
10 Portab	le Printers -			10:19:26
	d KANE IMPRINT er includes an integral IR	A REL		PETROL
transmitter	r that is compatible with two	82	%	0.74
infrared battery powered printers so that results can be recorded anywhere.		CO2 HC	% ppm	13.4 08
		CO CO	%	0.43
KMIRP	Uses thermal paper.	Сок	%	0.46
IMPRINT	Uses standard paper roll and ink ribbon.	Lambda NOX	ppm	1.027 183



# Making emission testing easy and affordable

### Kane Hand Held Exhaust Gas Analyser Range

Product Selection:					
	OIML C	OIML CLASS 1		Standard	
	Auto 5-1	Auto 4-1	Auto 5-2	Auto 4-2	
Measured Gases	CO/CO2/O2/HC/NOx	CO/CO2/02/HC	CO/CO2/O2/HC/NOx	CO/CO2/02/HC	
OIML Class 1 Certificate	<i>v</i>	<b>v</b>	Class 1 Accuracy	Class 1 Accuracy	
Corrected CO	<i>v</i>	<b>v</b>	<ul> <li>✓</li> </ul>	<b>v</b>	
Test Result Storage - 255 Tests	<ul> <li>✓</li> </ul>	<b>v</b>	<ul> <li>✓</li> </ul>	<b>v</b>	
Auto Store	<ul> <li>✓</li> </ul>	<b>v</b>	<ul> <li>✓</li> </ul>	<b>v</b>	
PC Compatible	<ul> <li>✓</li> </ul>	<b>v</b>	<ul> <li>✓</li> </ul>	<b>v</b>	
Infra Red Printer Compatible	V	<b>v</b>	✓	<b>v</b>	
Measures RPM 2, 4 Stroke, DIS	<ul> <li>✓</li> </ul>	<b>v</b>	<ul> <li>✓</li> </ul>	✓	
Measures Oil/Exhaust Temperature	<ul> <li>✓</li> </ul>	<b>v</b>	<ul> <li>✓</li> </ul>	<b>v</b>	
Fast Warm Up (150 seconds)	<i>v</i>	<b>v</b>	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	
Fuel Types: Petrol/LPG/CNG/Diesel*	V	✓	✓	<b>v</b>	
Power Supply Internal Battery/12v/Mains	V	✓	<ul> <li>✓</li> </ul>	<b>v</b>	
Carry Case - Laptop style softcase	V	✓	<ul> <li>✓</li> </ul>	<b>v</b>	
Exhaust Probe - Stainless Steel	V	✓	V	~	

\*HC is not displayed in diesel mode

# Gas Analyser as a Diagnostic Tool

Using the gas analyser as a diagnostic tool enhances its use. Some key faults that have an effect on gas emissions are listed in the table below.

- 1. Rich mixture
- 2. Weak Mixture
- 3. Ignition Missfire
- 4. Fuel Mis-magagement
- 5. Tight Valve Clearance
- 6. Incorrect Ignition Timing
- 7. Incorrect Valve Timing

Faulty Catalytic Convertor

In a busy multi-bay workshop there is no need to shuffle vehicles around to get them close to the 'big-box' analyser. Vehicles can even be tested outside on the forecourt and for difficult intermittent faults, exhaust gases can be sampled whilst the vehicle is being driven. This makes the analyser ideal for all types of repair, either in a workshop or mobile.



# **OIML R99 Class 1 Analysers**

The Auto 4-1 and Auto 5-1 series have been certified to be compliant with OIML R99 Class 1 (ISO 3930), under Test Report No N0356 of January 2001 issued by the duly authorised and approved OIML test body SIRA Test and Certification Ltd of the UK.

Compliance to OIML standards is often a requirement for regulated emission testing programmes around the world. Each analyser is supplied with a fully traceable calibration certificate.

# References from around the world

- Active Kane brand distribution network around the world
- Approved supplier to the FORD Group under the European EQS programme and Perusahaan Otomobil Nasional Berhad (PROTON) of Malaysia
- Supplier to several major OEM's operating in the Automotive Aftermarket for tools and Equipment
- Supplier to the Republic of the Philippines Department of Transportation & Communications with reference to the Implementation of Clean Air Act (CAA) Rules and Regulations
- Supplier for the Vehicle Emissions Testing (VET) component of the Cairo Air Improvements Project (CAIP), Cairo, Egypt
- Supplier to the Department of Land Transportation, Bangkok, Thailand
- Major supplier to Motorbike and Off-The-Road Vehicle workshops

## Making emission testing easy and affordable

